

2008 Toyota Camry Hybrid

Fluids

FLUID CAPACITIES

Air Cond Refrigerant

Application	Volume
All Applicable Models	1.25LBS. (0.6KG)
R-134a	

Automatic Transmission Fluid

Application	Volume
Trans Mfr CD U250E - Drain and Refill	3.70QTS. (3.5L)
TOYOTA Genuine Automatic Transmission Fluid Type WS	
Hybrid,Trans Mfr CD P311 - Drain and Refill	4.30QTS. (4.1L)
TOYOTA Genuine Automatic Transmission Fluid Type WS	
The fluid capacity is the quantity of reference.	
Trans Mfr CD U660E	6.87QTS. (6.5L)
TOYOTA Genuine Automatic Transmission Fluid Type WS	
The fluid capacity is the quantity of reference.	

Brake Fluid

Application	Volume
All Applicable Models	Top-Off As Required
DOT 3 Brake Fluid	

Engine Coolant

Application	Volume
2.4L Eng	6.60QTS. (6.2L)
TOYOTA Super Long Life Coolant or equivalent	
DO NOT use plain water alone.	
3.5L Eng	9.50QTS. (9.0L)
TOYOTA Super Long Life Coolant or equivalent	
DO NOT use plain water alone.	

Engine Oil

Application	Volume
2.4L Eng - Drain and Refill,w/o Filter	4.30QTS. (4.1L)
SAE 5W-20 or 0W-20	
2.4L Eng - Drain and Refill,w/Filter	4.50QTS. (4.3L)
SAE 5W-20 or 0W-20	
3.5L Eng - Drain and Refill,w/o Filter	6.00QTS. (5.7L)
ILSAC GF-4 SAE 5W-30	
3.5L Eng - Drain and Refill,w/Filter	6.40QTS. (6.1L)
ILSAC GF-4 SAE 5W-30	

Fuel Tank

Application	Volume
Hybrid	17.20GALS. (65.1L)

Manual Transmission Fluid

Application	Volume
All Applicable Models	2.60QTS. (2.5L)
API - GL-4 or GL-5, SAE 75W-90	

Power Steering Fluid

Application	Volume
All Applicable Models	Top-Off As Required
Automatic Transmission Fluid DEXRON II or DEXRON III	

Wash Fluid

2008 Toyota Camry Hybrid

Fluids

Application	Volume
All Applicable Models	Top-Off As Required
Plain water	
In cold areas where temperatures range below the freezing point, use washer fluid containing antifreeze.	